

**DESCRIPTION :**

BITAAID is an acrylic-bonding agent for mixing with regular cement, mortar and concrete surface. BITAAID provide a key for flexibility, waterproofing and attachment to new and old concrete and cementitious

**USER APPLICATION :**

BITAAID is an acrylic-bonding agent for cement, mortar and concrete, tiles adhesive, waterproof concrete and renders.

**INSTALLATION :**

- For screed and mortars, 1 kg mixed with 10 liter of clean water. Use mixture for wetting the screed and mortar.
- For tile adhesive, 1 kg mixed with 10 liter of clean water, use the mixture with cement and fine sand. Mix till you have tick homogeny pasta. Apply the pasta with a toothed trowel of  $\pm 5$  mm on the surface. Press the tiles into the pasta.
- For waterproof and concrete or renders, mix BITAAID into the ready concrete / slurry a ratio 1 kg for 50 kg of cement.
- As bonding agent between old and new concrete, paint one layer of BITAAID on the receiving part of the old concrete. Wait till dry before pouring the concrete.

**PACKING :**

2 Kg, 5 Kg, and 20 Kg

**CONSUMPTION :**

1 kg cover approx 1m<sup>2</sup>, depends the area.

**HANDLING & STORAGE :**

This product has a shelf life or 12 months if kept in dry cool place in the original packaging. In more extreme conditions this period might be shortened. Keep out of reach of children.

**CERTIFICATION :**

Comprised in the Balai Besar Penelitian dan Pengembangan Industri Bahan dan Barang Teknik (B4T) Bandung.

