

DESKRIPSI :

BITAGROUT adalah nat keramik berbahan dasar semen dengan formulasi bahan baku pilihan diperkaya additive polymer dibuat oleh tenaga ahli yang berpengalaman dengan pengawasan teknologi Belgia sehingga menghasilkan grouting yang kuat.

KOMPOSISI

BITAGROUT	KERAMIK
1 Kg = 5 - 6 m ²	60 x 60 cm
1 Kg = 7 - 8 m ²	40 x 40 cm
1 Kg = 8 - 9 m ²	30 x 30 cm

KEGUNAAN :

BITAGROUT dibuat khusus untuk mengisi nat keramik, marmer, mosaik granit dan sejenisnya baik interior maupun eksterior, sangat cocok untuk area basah seperti kolam renang.

KEUNGGULAN :

BITAGROUT memiliki daya rekat kuat, tahan ultra violet, kedap air, anti jamur, mudah dipasang dan ramah lingkungan.

CARA PENGGUNAAN :

- Campurkan BITAGROUT dengan air bersih, dengan komposisi 1 Kg BITAGROUT : 320 ml air bersih.
- Aduk hingga membentuk pasta dan diamkan selama 2 (dua) menit sebelum digunakan.
- Isilah nat dengan pasta BITAGROUT sambil ditekan agar nat terisi dengan penuh dan merata.
- Gunakan kape, spon lembab atau lap basah untuk membersihkan keramik dari sisa kotoran pasta
- Bersihkan alat kerja menggunakan air bersih.

KEMASAN : Tersedia dalam kemasan 1 Kg



CARA PENYIMPANAN :

Simpan di tempat yang sejuk dan kering, hindari dari sumber panas, dan jauhkan dari jangkauan anak-anak.

SERTIFIKASI :

Telah diuji di Balai Besar Penelitian dan Pengembangan Industri Bahan dan Barang Teknik (B4T) Bandung.



Disclaimer: the use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specification are subjected to changes without prior notice.





-  **Cementbase**
-  **Tahan Sinar UV**
-  **Daya Rekat Kuat**
-  **Mudah Dipasang**
-  **Daya Tahan Sangat Kuat**
-  **Kedap Air**
-  **Ramah Lingkungan**



Nat Keramik



Masa Pengeringan:
5-10 Jam tergantung cuaca



Diproduksi oleh:
PT BITAL ASIA
Jl. Raya Legok Km. 7,9, Tangerang
15820, Banten - Indonesia
www.bitalasia.com



Disclaimer: the use of this product is beyond the manufacturer's control and liability is restricted to the replacement of material proven faulty. The manufacturer is not responsible for any loss or damage arising from incorrect usage. Specification are subjected to changes without prior notice.

